Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address:	Gem Imports Ltd,	Unit A Capitol Way, S	75 3FG Barnsley	
Model identifier: El	LE0441/OB			
Type of light source	:			
Lighting technology used:		LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)		GU10		
Mains or non-mains:		MLS	Connected light source (CLS):	No
Colour-tuneable light source:		No	Envelope:	-
High luminance light source:		No		
Anti-glare shield:		No	Dimmable:	No
		Product para	ameters	
Parameter	,	Value	Parameter	Value
	<u>.</u>	General product	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		5	Energy efficiency class	F
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		430 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	
On-mode power (P _{on}), ex- pressed in W		5.0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0.00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second dec- imal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	leight	50	Spectral power dis-	See image in last
	Vidth	55	tribution in the	page
separate con- trol gear, light-	epth	55	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any			
(millime- tre)			
Claim of equivalent power(a)	Yes	If yes, equivalent power (W)	40
		Chromaticity coordi-	0,440
		nates (x and y)	0,403
Parameters for LED and OLED light source	es:		
R9 colour rendering index value	0	Survival factor	1.00
the lumen maintenance factor	0.95		
Parameters for LED and OLED mains ligh	t sources:		
displacement factor (cos φ1)	0.00	Colour consistency in McAdam ellipses	6
Claims that an LED light source	_(b)	If yes then replace-	-
replaces a fluorescent light		ment claim (W)	
source without integrated bal-last of			
a particular wattage.			
Flicker metric (Pst LM)	1.0	Stroboscopic effect	0.4
		metric (SVM)	

(a)₁-': not applicable; (b)₁-': not applicable;